

Safety Data Sheet (SDS)

According to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Section 1: Identification of the Substance/Mixture and the Company/Undertaking

Product Name: UHW 2K Aliphatic Topcoat B

Product Code: 57-0120-B

Rio Flooring Systems Inc.

2926 Chester Avenue

Cleveland, OH 44114

United States

Email: info@riofloor.com

Phone: (888) 278-2183



Chemtrec: 1- 800-424-9300

Chemtrec Global: 1-703-741-5970

Section 2: Hazard(s) Identification

GHS Ratings:

Flammable liquid	4	Flash point $\geq 60^{\circ}\text{C}$ (140°F) and $\leq 93^{\circ}\text{C}$ (200°F)
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity ≥ 3 , Iritis > 1.5
Skin sensitizer	1	Skin sensitizer
Mutagen	1B	Known to produce heritable mutations in human germ cellsSubcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1B	Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity
Reproductive toxin	1B	Presumed, Based on experimental animals

GHS Hazards

H227	Combustible liquid
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage
H340	May cause genetic defects
H350	May cause cancer
H360	May damage fertility or the unborn child

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P235	Keep cool
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P310	Immediately call a POISON CENTER or doctor/physician
P321	Specific treatment, see supplemental first aid information.
P363	Wash contaminated clothing before reuse
P302+P352	IF ON SKIN: Wash with soap and water
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention

P333+P313
P370+P378

P405
P403+P235
P501

If skin irritation or a rash occurs: Get medical advice/attention
In case of fire: Use alcohol resistant foam, dry chemical, carbon dioxide (CO₂), dry sand for extinction
Store locked up
Store in a well ventilated place. Keep cool
Dispose of contents/container in accordance with local/regional/national/international regulations. Manufacturer/supplier or the competent authority to specify whether disposal requirements apply to contents, container or both.

Signal Word: Danger



Unnecessary exposure to any chemical should be avoided. NOTICE--Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after applicable limits. Follow respirator manufacturer's directions for respirator use.

Section 3: Composition/Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Propylene Carbonate	108-32-7	40.00% - 50.00%
Proprietary material	Proprietary material	30.00% - 40.00%
Modified Carbonate Bis-Oxazolidine	145899-78-1	5.00% - 10.00%
Nonhazardous Material	Nonhazardous Material	1.00% - 5.00%
Solvent naphtha, petroleum, light aromatic	64742-95-6	1.00% - 5.00%
2-Isopropyl-3-oxazolidineethanol	28770-01-6	0.10% - 1.00%
Dibutyltin dilaurate	77-58-7	0.10% - 1.00%
Diisobutyl ketone	108-83-8	0.10% - 1.00%
Cumene	98-82-8	0.00% - 0.10%

Section 4: First Aid Measures

After Inhalation: Immediately supply fresh air. Keep patient in restful and comfortable position for breathing. If required provide artificial respiration, although this may be dangerous. Consult doctor if symptoms persist.

After Eye Contact: Immediately rinse opened eye(s) for several minutes under running water. Use lukewarm water if possible. Remove contact lenses if worn. Get medical attention.

After Skin Contact: Remove contaminated clothing and shoes. Immediately wash with water and soap, rinse thoroughly. If skin irritation continues, consult a doctor.

After Swallowing: Immediately get medical attention. Call a poison center or physician. Rinse out mouth and then drink small amounts of water. Do not induce vomiting as this may be dangerous. Aspiration hazard if swallowed, can enter lungs and cause damage. If vomiting occurs, the head should be kept low to avoid vomit entering the lungs. Maintain an open airway.

Notes to Physician: Treat symptomatically

Section 5: Firefighting Measures

Flash Point: 76 C (169 F)

LEL: 5.00

UEL: 21.00

Extinguishing Media:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

Special Hazards Arising from the Substance of Mixture:

Formation of toxic gases is possible during heating or in case of fire. Check flammability in section 2 of this sheet.

Mixture in sealed and heated containers may cause explosion hazard .

Hazardous Combustion Products may include the following:

Carbon oxides. Metal oxide(s). Nitrogen oxides.

Can form explosive vapor-air mixtures

Vapors are heavier than air and may spread along floors . Vapors may travel considerable distance to source of ignition and flash back.

Advice for Firefighters:

Clear fire area of unprotected personnel. Containers that are exposed to intense heat should be cooled with water.

Avoid spreading burning liquid with the water used for cooling purposes . Do not enter fire area without protective gear. Fight fire from safe distance or a protected location.

Fire Equipment:

Wear self-contained respiratory protective device . Dispose of fire debris and contaminated fire fighting water in accordance with official regulations .

Section 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Wear protective clothing.

Keep from contacting skin or eyes.

Avoid breathing vapors, mist, or gas.

Ensure adequate ventilation.

Evacuate personnel to safe areas.

If any equipment is necessary, ensure that it is non-sparking and electrically-protected .

Environmental precautions:

Do not allow product to reach sewage system or any water source.

In case of seepage into the ground inform responsible authorities

Prevent from spreading (e.g. by damming-in or oil barriers).

Keep contaminated washing water and dispose of appropriately

Methods and material for containment and cleaning up:

Ensure adequate ventilation

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste.

Do not flush with water or aqueous cleansing agents.

Send for recovery or disposal in suitable receptacles according to local, state and federal regulations .

Section 7: Handling and Storage

Handling:

Apply proper ventilation, possibly combined with local exhaust.

Do not eat, smoke or drink during use.

For personal protection see Section 8.

Keep away from sources of ignition.

Keep material out of reach of children.

Use only explosion proof equipment.
Wash thoroughly after handling.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges by bonding and grounding product containers before and during material transfers.

Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities:

Storage:

Keep away from sources of ignition - no smoking. Store in a cool, well ventilated place. Keep in original, closed packaging. Comply with governmental regulations.

Keep container tightly closed. Store out of direct sunlight, between 40 and 90F.

Specific end use(s): FOR INDUSTRIAL USE ONLY!

Section 8: Exposure Controls/Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Propylene Carbonate 108-32-7	Not Established	Not Established	Not Established
Proprietary material Proprietary material	Not Established	Not Established	Not Established
Modified Carbonate Bis- Oxazolidine 145899-78-1	Not Established	Not Established	Not Established
Nonhazardous Material Nonhazardous Material	Not Established	Not Established	Not Established
Solvent naphtha, petroleum, light aromatic 64742-95-6	Not Established	Not Established	Not Established
2-Isopropyl-3- oxazolidineethanol 28770-01-6	Not Established	Not Established	Not Established
Dibutyltin dilaurate 77-58-7	Not Established	Not Established	Not Established
Diisobutyl ketone 108-83-8	50 ppm TWA; 290 mg/m3 TWA	25 ppm TWA	NIOSH: 25 ppm TWA; 150 mg/m3 TWA
Cumene 98-82-8	50 ppm TWA; 245 mg/m3 TWA	50 ppm TWA	NIOSH: 50 ppm TWA; 245 mg/m3 TWA

Ventilation:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

Personal Protective Equipment/General Protective and Hygienic Measures:

Respiratory Protection:

In outdoor or open areas use (NIOSH/MSHA approved) mechanical filter respirator to remove solid airborne particles of overspray during spray application. In restricted ventilation areas use (NIOSH/MSHA approved) chemical-mechanical filters designed to remove a combination of particulate and gas and vapor. In confined areas use (NIOSH/MSHA approved) airline type respirators or hoods. Respiratory protection may also be necessary in any later manufacturing operations in which the product may become airborne in the form of vapor or dust.

Protective Gloves:

Protective gloves are required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile. An apron should be worn to avoid skin contact. (Consult your safety equipment supplier.)

Eye Protection:

Avoid contact with eyes. Wear goggles if there is a likelihood of contact with eyes. (Consult your safety equipment supplier.) Eyewash stations and safety showers should be readily available in use and handling areas.

Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

Body Protection:

Chemically resistance gloves, apron and safety goggles are recommended. Type of protective equipment should be selected based on concentration amount and conditions of use of this material.

Contaminated Gear:

Dispose of in accordance with official regulations.

Section 9: Physical and Chemical Properties

Appearance Liquid	Odor Typical Solvent
Physical State Liquid	Vapor Pressure 9.8 mmHg
Boiling Range 148 to 177 °C	Specific Gravity (SG) 1.137
Coating VOC (as supplied) 0.31 lb/gl	Coating VOC (EPA 0.75 calculation) lb/gl

Section 10: Stability and Reactivity

Incompatibilities:

Avoid contact with strong oxidizing agents.

Hazardous Decomposition:

Thermal decomposition may form toxic materials; carbon dioxide, carbon monoxide, various hydrocarbons, etc.

Hazardous polymerization will not occur.

Section 11: Toxicological Information

Mixture Toxicity

Component Toxicity

77-58-7

Dibutyltin dilaurate

Oral LD50: 45 mg/kg (Rat) Dermal LD50: 630 mg/kg (Rabbit)

Routes of Entry:

Target Organs:

Eyes

Kidneys

Liver

Central Nervous System

Skin

Respiratory System

Effects of Overexposure

Carcinogenicity:

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
64742-95-6	Solvent naphtha, petroleum, light aromatic	1 to 5%	Solvent naphtha, petroleum, light aromatic: EU REACH: Present (P)
98-82-8	Cumene	0 to 0.1%	Cumene: IARC: Possible human carcinogen OSHA: listed

Section 12: Ecological Information

Environmental Impact Statement/Toxicity:

Aquatic toxicity: No further relevant information available

Persistence and degradability: No further relevant information available

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Other adverse effect: No further relevant information available

Component Ecotoxicity

Solvent naphtha, petroleum, light aromatic	96 Hr LC50 Oncorhynchus mykiss: 9.22 mg/L 48 Hr EC50 Daphnia magna: 6.14 mg/L
Diisobutyl ketone	96 Hr LC50 Oncorhynchus mykiss: 140 mg/L [semi-static] 96 Hr EC50 Pseudokirchneriella subcapitata: 100 mg/L
Cumene	96 Hr LC50 Pimephales promelas: 6.04 - 6.61 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 4.8 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 2.7 mg/L [semi-static]; 96 Hr LC50 Poecilia reticulata: 5.1 mg/L [semi-static] 48 Hr EC50 Daphnia magna: 0.6 mg/L; 48 Hr EC50 Daphnia magna: 7.9 - 14.1 mg/L [Static] 72 Hr EC50 Pseudokirchneriella subcapitata: 2.6 mg/L

Section 13: Disposal Considerations

Waste treatment methods:

Recommendation:

Must not be disposed of together with household garbage.

Do not allow product to reach sewage system.

Disposal of this product and any by-products must at all times comply with local, state and Federal regulations for hazardous wastes. All entities that store, transport or handle hazardous waste must take the necessary measures to prevent risks of pollution, release into the environment or damage to people and animals.

Contaminated Packaging:

Waste packaging should be recycled. Care should be taken when handling emptied containers that have not been cleaned. Empty containers retain some product residues. Vapor from that residue may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers.

Section 14: Transport Information

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	NOT	REGULATED		
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[2-[(1-mthylethyl)-3-oxazolidinyl] ethyl]hexane-1-2-diylbiscarbamate)	UN3082	III	9
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[2-[(1-mthylethyl)-3-oxazolidinyl] ethyl]hexane-1-2-diylbiscarbamate) MARINE POLLUTANT	UN3082	III	9

Section 15: Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Prop 65 - Chemicals Known to Cause Developmental Toxicity

- None

Prop 65 - Chemicals Known to Cause Cancer:

- None

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

- None

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

- None

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

- None

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

- None

- None

TSCA (Toxic Substances Control Act)

Country

USA

Regulation

Inventory - United States - Section 8(b) Inventory (TSCA)

All Components Listed

Yes

EU Risk Phrases

Safety Phrase

U.S. - SARA:

98-82-8 Cumene 0.0 - 0.1%

Section 16: Other Information

DISCLAIMER

THE INFORMATION CONTAINED HEREIN WAS RECEIVED FROM OUR RAW MATERIAL SUPPLIERS AND OTHER SOURCES. CONTINENTAL PRODUCTS MAKES NO EXPRESS OR IMPLIED WARRANTIES REGARDING THE ACCURACY OF THE ABOVE INFORMATION AND YOU SHOULD NOT RELY ON IT. YOU SHOULD TEST THIS PRODUCT FOR CHEMICAL COMPOSITION AND CONSULT APPLICABLE SAFETY AND MEDICAL STANDARDS AND PROFESSIONALS RELATED THERETO. CONTINENTAL PRODUCTS DOES NOT WARRANT THE SUITABILITY OF THE PRODUCT FOR ANY APPLICATION BY THE USER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.

Date revised: 2022-01-31

Reviewer Revision

Date Prepared: 2/15/2022